



[Home](#) · [About](#) · [Tipi](#) · [Yurt](#) · [Dome](#) · [Features](#) · [Gallery](#) · [Links](#)

- Yurt
- Yurt Notes
  - Introduction
  - Mongolian Terms
  - Yurt Details
  - Yurt Math
  - How to Calc
  - Yurt Calculator
  - Costs
  - Wheel / Toono
  - Wall / Khana
  - Door / Khaalga
  - Insulation
  - Slows
  - Floor
  - Attached Room
  - Modern vs. Traditional
  - Standard vs. Non-Standard
  - Erect the Yurt
  - Interior
  - References
- Yurt Diary
- Living Notes
- Material Notes

## Yurt / Ger Notes

written by Rene K. Mueller, Copyright (c) 2006, last updated November 12, 2007

### How to Calc

The height **h** is 140-180cm, or even 200cm, smaller yurts (e.g. 3-4m) arc lower, e.g. 6m often is 1.60 or more. The height is so low because the resulting room is better to heat, but for reason of comfort you may choose to have it your head height high.


Traditional yurt development comes from a given **w** khana-spacing and length of a khana-section, and then the amount of poles is calculated, e.g. 2-3 khana sections, or 4-6 khana sections for large yurt, then the poles are counted. I have prefered to define the yurt from the amount of poles for reasons of angle measurement and symmetry (e.g. multiple of 4 poles), to increase or decrease  $n_{poles}$  in order to make and see how large the spacing of **w** gets. The resulting **w** should be between 20-35cm in order to create a stable wall / *khana*, good stable laths may allow larger spacings of **w**.

Usually the roof poles lie on each lath junctions, which is arranged as crossed lattice. Modern yurts disregard this approach and lie the roof poles on the rope which holds the wall / *khana* together, this way one is very flexible to build with given parts (e.g. wall / *khana*, crown-wheel / *toono* etc) multiple sized yurts, but you sacrifice some of the stability of the lattice wall.

Traditionally and also for stability the wall lattice is spread so the crossing laths relate in 90° (*akhana*) angle, but you may have a shorter angle like 60-80° and have with shorter laths a higher wall.

The diameter of the crown-wheel / *toono* is traditionally 20% of the yurt diameter, but this is just a reference nothing more.

### Yurt Calculator



Edit the numbers in the yellow fields, and then press "calculate" button.

d = 192.88cm, h = 170cm,  $n_{poles}$  = 128,  $d_{wheel}$  = 192.88cm

height defined by   $h_{tot}$  = 226.53cm, or via   $\alpha_{roof}$  = 13°, (0..50°)

Hint: The larger the **d** diameter, the more poles you need, try a multiple of 4 for the roof pools ( $n_{poles}$ ). The resulting **w** should be between 20-35cm as mentioned to get a stable khana (e.g. diameter **cm** / 10 = poles gives **w** = 31cm).

Also, **w**<sub>wheel</sub> shouldn't be too small in order to assemble the roof poles on the roof/crown wheel, increase the roof/crown wheel diameter **d**<sub>wheel</sub> if necessary. Also, **akhana** you can alter, and increase **h** by a given **khana** (e.g. 2m **khana** with 90° gives **h** ~ 142cm, but with 83° you reach **h** ~ 150cm).

#### General:

total circumference **c** = 42.4m,  
 floor area  $A_{floor}$  = 143.11m<sup>2</sup>  
 total volume  $V_{total}$  = 317.87m<sup>3</sup>

#### Wall / Khana:

spacing of roof poles & khana **w** = 33.13cm,  
 length of khana lath **khana** = 203.38cm,  
 spacing between holes  $w_{khana-holes}$  = 30.18cm,  
 total 7 holes (extra 22cm left), with  $\alpha_{khana}$  = 66.4° angle  
 (if you change it,  again)

total of appr.  $n_{laths}$  = 281 khana laths required,  
 gives  $n_{khana-sections}$  = 9 khana-sections, when **khana-section** = 3m  
 (if you change it,  again).

#### Roof Poles / Uni:

Roof pole length  $l_{pole}$  = 604.14cm,  
 (add additional length for entering the crown-wheel / *toono* 3-4cm and the other end with cord 2-3cm, total e.g. 6cm)  
 angle between each pole  $\alpha_{poles}$  = 2.81°,  
 space between poles at the roof/crown wheel  $w_{wheel}$  = 4.48cm

### Canvas

The canvas has two main pieces: the roof, and the wall.

#### Roof Canvas

In order to calculate the angle  $\alpha_{cutoff}$  I simply calculate both circumferences, based on  $d_{roof}$  and **d**, and then subtract the later from the first, this is the length which is left and needs to be cut away:

$$\alpha_{cutoff} = (d_{roof} * \pi - d * \pi) * 360 / (d_{roof} * \pi)$$

$$w_{cutoff} = \sin(\alpha_{cutoff}/2) * l_{roof} * 2$$

Therefore

$l_{roof}$  = 698.8cm,  
 $d_{roof}$  = 1397.6cm,  
 $\alpha_{cutoff}$  = 12.26°,  
 $w_{cutoff}$  = 149.21cm

$A_{roof}$  = 153.38m<sup>2</sup> e.g. square canvas of 13.98 x 13.98m, appr. 41.96m<sup>2</sup> left over.

#### Lanewise

Use multiple lanes (common way to get canvas) as indicated to compose the shape:

$$n_{roof-lanes} = d_{roof} / w_{lane} \text{ (and round up)}$$

$$l_{net-lanes} = d_{roof} * n_{roof-lanes}$$

You can calculate more exact (approximate the circle without tilt cutoff  $\alpha_{cutoff}$ ):


#### Metric vs English System

As wood and other material is in the US still in feet and inches measured, may this small calculator assist you.

1397 cm = 44.23 ft

Enter your number, and hit ENTER or TAB

1 yard = 91.44cm, 1' or feet = 30.48cm,  
 1" or inch = 2.54cm, 1cm = 0.01m,  
 100cm = 1m



Wlane = 150cm, Wroofextra = 10cm, calculate lanes

Lane #1 = 8.76 x 1.5 m  
 Lane #2 = 11.63 x 1.5 m  
 Lane #3 = 13.27 x 1.5 m  
 Lane #4 = 14.09 x 1.5 m  
 Lane #5 = 14.28 x 1.5 m  
 Lane #6 = 14.26 x 1.5 m  
 Lane #7 = 13.78 x 1.5 m  
 Lane #8 = 12.59 x 1.5 m  
 Lane #9 = 10.45 x 1.5 m  
 Lane #10 = 6.47 x 1.5 m

whereas last lane has 6.47 x 0.72m left over.


Total length as one lane: 119.58 x 1.5m

Often canvas comes 1m - 2m (e.g. 1.60m) width, but can be hundreds of meter long. I recommend for the height of the yurt **h** not to go over the common 1.60m, e.g. I choose 1.50m so I have 2 times 5cm left top and bottom for the seam.

Note: You need to add extra length as you have to sew the roof canvas (enter 5-10cm less than the actual lane width for  $w_{lane}$ ), and also fold its seam two or four times, additionally, bought canvas usually shrinks 5-7%, so buy preshrunk canvas or shrink it (means wash it) **before** you cut.

Sewing: Either mark the middle line of each cut canvas lane (in the illustration the red line), and then align the lanes along this middle line or calculate the offset of each next layer to the previous; maybe also use needles to attach the next lane to sew, avoid wrinkles, with some practice with a sewing-machine you might do it without needles.

When working from top to bottom, next lane over previous lane, until you reach the center, then next lane under previous lane. For the rain cover you might use one big piece of canvas, instead to lay lanes to each other and leave a lot of seams where water can leak through.




In the real world application, you might **not** cut  $\alpha_{cutoff}$  away but just make a line cut, and let the two laps overlap each other, in this case you need an additional layer of cover, or bind it with a cord.

For the rain insulation I use a square blanket of synthetic and leave it in that shape and make **no** cut at all but fold it for the tilt and tie it with 4 or 6 cords to the bottom of the yurt.

The cotton interior roof canvas I compose with multiple canvas lanes, and for a roof angle  $\alpha_{roof}$  of 25° I let the canvas leave without cut or folding the spare, the canvas did hang a bit between each roof pole. For larger roof angles you may consider to truncate the canvas to fit it more closely.

### Traditional Lanewise

Traditional roof canvas is sewed lane wise, e.g. you attach various lanes until you reach the center, that part of the canvas is laid onto the yurt skeleton, and the next lanes are individually matched to that form and step by step added. It's a time consuming procedure, and the roof canvas fits closely but becomes more inflexible. As I mentioned before, for 25° roof angle a flat circle formed canvas is sufficient, the extra canvas (vs cone) is distributed evenly among all the roof and hangs a bit (1-2cm) down between the roof poles.



### Pieslice-wise

If the roof is small enough and match the width of the canvas, or the canvas available makes it more suitable, you can also make it pieslice-wise and arrange the pieces so it fits the lane nicely, with little leftover.


slices = 10, recalculate

Outer = 353.36cm

Inner = 47.87cm

$l_{pole} = l_{pie} = 604.14cm$ , and add 10-15cm ( $w_{roofextra}$ ) to have it overlap to the wall

The pieslice-wise approach can be used for inner but also outer rain canvas, yet in case a 100% leak-free seam is then required, and since the seams run top to bottom of the roof and not sidewise this is doable. I use the pieslice-wise approach for the thermal insulation layer.



As you see, for each individual layer (rain canvas, insulation, and interior) you can use the calculator. I use for

- rain cover: one piece of canvas of PE ( $d_{roof} \times d_{roof}$ )
- thermal insulation: lanewise bubblewrap
- thermal insulation: pieslice, filled blankets
- interior cotton: lanewise

### Wall Canvas


This is rather simple, it's rectangular, and  $e$  (circumference) times  $h$  of the lattice wall / *khana*. With your numbers, the wall canvas is  $42.4 \times 1.7m$  or  $A_{wall} = 72.08m^2$ .

Best you choose  $w_{lane}$  the same as  $h$ , then you can use one lane for the entire wall canvas; otherwise you require to sew lot's of vertical lanes together to achieve  $h$ , with your  $w_{lane}$  you do 29 lanes for the entire wall canvas.

You may subtract the door width (discussed later in more detail), but I recommend you plan with extra length, it's easier to cut than add more canvas later. I used 10m long sections, attached short cords in order to bind it to the main rope, you can also bind to the roof-poles.

### Total Canvas

Total canvas of approx.  $168.88 \times 1.5m$



### Costs

You can get an approximate cost overview, choose your own currency (US\$, €, CHF etc).

Cost per canvas meter: 6.00 total cost canvas: 809.9

Cost per roof pole:  total cost roof poles:   
 Cost per khana lath:  total cost khana:

**Total Cost Canvas/Poles/Khana:**

You still need:

- . crown wheel aka *toono*
- . door aka *khaalga*
- . multiple layers (e.g. interior, insulation layer)
- . floor

Often the canvas may be the most expensive part of your yurt so it makes sense to really get a good and priceworthy source for the cotton, the same for the raincover.

My 6.4m diameter yurt with 64 poles did cost approx. CHF 1000 or US\$ 800 or € 670 (bamboo poles for roof & wall, PE as rain cover, wholesale cotton 1.5m wide etc), see details in my [yurt diary](#).

[Next Page >>](#)

Page << [Prev](#) | [1](#) | [2](#) | [3](#) | [4](#) | [5](#) | [6](#) | [7](#) | [Next](#) >>

**Content:**

- . [Page 1: Introduction, Mongolian Terms, Yurt Details, Yurt Math](#)
- . [Page 2: How to Calc, Yurt Calculator, Canvas, Costs](#)
- . [Page 3: Wheel / Toono, Traditional, 8 Segment Wheel, Multiple Layers, Other Ways, Roof Weight, Skylight / Toono Cover ...](#)
- . [Page 4: Wall / Khana, Bamboo Lattice Wall, Flat Timber Lattice Wall, Termination of Wall Sections ...](#)
- . [Page 5: Insulation, Rain Cover, Thermal Insulation, Interior, Case Rating 1: Bubble-Wrap & PE Rain-Cover ...](#)
- . [Page 6: Stove, Fan, Floor, Floor Layers, Attached Room, Math, Calculator, Example, Modern vs. Traditional ...](#)
- . [Page 7: Erect the Yurt, Preparing the Ground, Floor, Lattice Wall, Crown-Wheel, Layers, Ropes & Tension Ribbons ...](#)

[Home](#) · [About](#) · [Tipi](#) · [Yurt](#) · [Dome](#) · [Features](#) · [Gallery](#) · [Links](#)

[Print](#)  · [Contact](#) 



Copyright © 2005, 2006, 2007 by René K. Müller, All Rights Reserved  
 Graphics & illustrations made with Inkscape, Tgif, Gimp, PovRay, GD pm  
 Web-Site powered by FreeBSD & Debian Linux - 100% Open Source